

Pennine uPVC General Purpose Ducts

Material & Technical Data Sheet

Pennine uPVC GP duct can be used for drainage and general purpose piping applications.

All products are manufactured within the scope of Pennine's ISO 9001 quality system, but do not meet BS EN 61386-24:2010

Standard duct colour is black, with other colours available on request.

Ducts are supplied bundled, packed in wood U-frames constrained using steel strapping.

Duct bundles must be stored on level firm ground and may be stacked up to 3 high subject to customer site risk assessment



Product Code	Product Description	Nominal gms/metre	Pack Qty
UG054U60X	GP - 53.9mm diam Black-Socketed 6m	460	371
UG089U60X	GP - 88.9mm diam Black-Socketed 6m	830	138
UG110U60X	GP - 110mm diam Black-Socketed 6m	1180	95
UG160U60X	GP - 160mm diam Black-Socketed 6m	2130	46

Pennine uPVC GP ducts are tested in-house for reversion - <5% at 150°C , impact strength - 1.5kg x2m , and ovality - <1.5mm.

CoC can be issued with each shipment to confirm pipes meet the relevant

Pennine Manufacturing Ltd, Fold Mill, Bradley Lane, Little Lever, Bolton, BL2 6RA.
T: (+44) 01204 361 547 United Kingdom.

Company Number 01240154

